Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark:	HEAVN GmbH

Supplier's address:	Customer Support, Miesbacher Str. 34, 83620 Feldkirchen-Westerham, DE

Model identifier:	HEAVN One LED HCL+

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	PCB mit Steck-verbinder		
Mains or non-mains:	NMLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters			
Parameter	Value	Parameter	Value
General product parameters:			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	18	Energy efficiency class	D
Useful luminous flux (ϕuse), indicating if it refers to the flux in a sphere (360º), in a wide cone (120º) or in a narrow cone (90º)	2 782 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	1800...6500
On-mode power (P_{on}), expressed in W	17,9	Standby power (P_{sb}), expressed in W and rounded to the second decimal	0,00
Networked standby power (P_{net}) for CLS, expressed in W and rounded to the second decimal	0,04	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	94
Outer dimensions without separate control gear, light-	Height 25	Spectral power distribution in the range 250 nm to 800 nm, at full-load	See image in last page
	Width 670		
	Depth 32		

ing control parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power[a]	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,320 0,340
Parameters for LED and OLED light sources:			
R9 colour rendering index value	74	Survival factor	-
the lumen maintenance factor	-		

[a]'-' : not applicable;

[b]'-' : not applicable;

HEAVN One LED HCL+